

**TOPCon**

High Efficiency Module

23.2%

Maximum Efficiency

15 YEARS

Product Warranty

Hitouch^{6RN}

HN21RN-66H

605-625W

**Higher Power Output**

Higher module conversion efficiency benefit from bigger wafer and half-cell structure.

MBB technology enhances current collection with lower series resistance.


**Excellent Temperature Coefficient**

Lower operating temperature and temperature coefficient increases the power output.

**Lower Hot Spot and Crack Risk**

Reduce hot-spot risk with optimized electrical design and lower operating current.

Reduce crack risk by MBB solar cell design.

Power Warranty

15-year product warranty



30-year linear power output warranty

Insurance**Certificates****About Hanersun**

Hanersun is a world-leading energy technology company, with a business scope from the R&D and intelligent manufacturing of solar modules, energy storage products, to comprehensive energy solutions.

Electrical Characteristics


Module Type	HN21RN-66H605W		HN21RN-66H610W		HN21RN-66H615W		HN21RN-66H620W		HN21RN-66H625W	
Testing Condition	STC	NMOT								
Maximum Power (Pmax)	605	457	610	461	615	464	620	468	625	472
Maximum Power Voltage (Vmp)	40.41	37.77	40.59	37.95	40.77	38.10	40.95	38.25	41.13	38.44
Maximum Power Current (Imp)	14.98	12.10	15.03	12.15	15.09	12.19	15.15	12.24	15.20	12.28
Open-circuit Voltage (Voc)	48.52	46.05	48.72	46.24	48.92	46.43	49.12	46.62	49.32	46.81
Short-circuit Current (Isc)	15.88	12.83	15.94	12.88	16.00	12.93	16.06	12.98	16.12	13.03
Module Efficiency(%)	22.4%		22.6%		22.8%		23.0%		23.2%	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.

*Measuring tolerance: 0 ~ +5W

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.**Mechanical Parameters**

Solar Cells	Monocrystalline (210R)
No. of Cells	132 [2 x (11 x 6)]
Module Dimensions	2382*1134*30mm
Weight	28.2kg
Glass	3.2mm, High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA/POE
Backsheet	White
Frame	Anodized Aluminium Alloy
J-Box	IP68
Output Cable	4.0mm ²
(Including Connector)	Length Portrait:300/300mm (can be customized)
Connector	MC4 Compatible

Dimensions (Unit: mm)

Front View

Temperature Ratings

NMOT (Nominal operating cell temperature)	43°C(±2°C)
Temperature Coefficient of Pmax	-0.280%/°C
Temperature Coefficient of Voc	-0.230%/°C
Temperature Coefficient of Isc	+0.045%/°C




(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

Operating Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	35A
Bifability	/

Packaging

Pcs per Pallet:	37
Pcs per 40' HC:	740

I-V Curves of PV Module (620W)**P-V Curves of PV Module (620W)**

Back View